

DESCRIPTION

STROLLER

5

TECHNICAL FIELD

The present invention relates to a stroller and, more particularly, to a stroller having a carrier basket.

BACKGROUND ART

10 Generally, a stroller for taking a baby outdoors for a walk or shopping is provided with a carrier basket placed under a seat to contain baggage and various necessities.

Referring to Fig. 14 showing such a stroller in a
15 perspective view, the stroller has right and left front legs 12 provided with front wheels 11, right and left rear legs 14 provided with rear wheels 13, a substantially U-shaped handle 15, right and left armrests 16, and a detachable guard arm 17 extended
20 between the armrests 16. Rear ends of the armrests 16 are pivotally joined to lower ends of right and left side pipes 18 of the handle 15, respectively. Upper ends of the front legs 12 are pivotally joined to front ends of the armrests 16, respectively. Upper ends of the
25 right and the left rear legs 14 are pivotally joined to middle parts of the armrests 16, respectively. Lower ends of L-shaped brackets 19 are pivotally joined to middle parts of the rear legs 14, respectively. Lower ends of the right and the left side pipes 18 are
30 pivotally joined to middle parts of the brackets 19, respectively. When the stroller is unfolded, locking members 20 slidably mounted on lower parts of the side pipes 18 engage with upper locking parts of the brackets 19 to keep the stroller unfolded.

35 A front stretcher 21 is extended between the right and the left front legs 12, and a rear stretcher 22 is

Sub Spec
Entry Approved
FBV 2/27/06